

**More safe and more convenient with
EZON Fingerprint Verification Door Lock.**

**The porch where built-in EZON Fingerprint Verification
Door Lock will prove your pride of elegant living life**

- More safe with the fingerprint! More convenient with Digital!
- Hi-tech Digital Fingerprint Verification Door Lock
- Even the fingerprint sensor is not operated!
- User selectable various door release method
; 4~12digits password.
- Luxurious style and hidden safe tech
- Auto sliding cover
- Invasion Detecting Alarm
- Automatic Locking and Relocking
- Forced Locking Both of Inside and Outside
- Unique Designed Mortis Lock
- Indoor Wireless Remote Controller (Optional)

**Benefit from the advanced future!
Intelligent Fingerprint Door Lock - EZON**

More Convenient, Higher Security

The Door Opened with your Fingerprint and Password
Passes on your Happiness and Security to the
innovative Digital Technology of EZON.

Open the door with your fingerprint.



We can open the locked door with fingerprint. Having recorded the whole family fingerprints, we can open the door easily only with fingerprints. (It is possible to record 40 in total)

Open the door with pin number.



We can record wishing pin number and then input the recorded pin number to open the door conveniently.

Function of double-locking.



If we use double-locking at night, it can make sure security. Because the door can not be opened from the outside.

Prevent the mischief of children and outsiders



If using the unrecorded pin number or fingerprint to open the door more than three times, the alarm will make a sound and the power will be cut off automatically after 1 minute.

Inside ▶



◀ Outside

SHS-DL20

- Size: 81(W) x 329(H) x 84(D)mm
- Power: DC 6V(Alkaline AA Battery 8pcs)

Specifications

Number combination	4~12 digits number combination
User capacity (Maximum Registration)	40 fingerprints 1 Number combination
Method of Fingerprint	Optical
Remote controller	447.7375MHz, DV 4.6V, 100m (Effective Distance)
Dimension (Datum of handle)	Outside : 81 x329 x84 (mm: W x H x D) Inside : 82 x299 x84 (mm: W x H x D)
Door depth	38 ~ 50(mm) / more than 50 (mm) is option
Material	Zinc alloy
Color	Dark Grey
Temperature	-25 °C ~ +60 °C(Outside) -10 °C ~+55 °C(Indoor)
Humidity	90%
Power	DC 6V(Alkaline AA,LR6 Battery 8pcs)
False Rejection Rate	0.01%
False Acceptance Rate	0.001% or Less
Sensor speed	Less than 1 second
Duration(Battery)	Average 3,650accesses (The battery duration is about 10months)
Packing Box Size	300 x375 x105 (mm: W x H x D)

SEOUL COMMTECH CO., LTD.

448-11, Seongnae 3dong,
Kangdong-Ku, Seoul, Korea 134-033
Tel : +82-2-2225-6709
Fax: +82-2-2225-6073
E-mail : yt05.kim@samsung.com
<http://www.scommtech.co.kr>